

Metering valve

MO


Positive displacement injectors (PDI) for oil. Up to nine different outputs per stroke are available. Can select proper discharge volume for all of your needs.

Specifications

Discharge volume	0.01,0.03,0.05,0.1,0.2,0.3,0.5,1.0,1.5ml/stroke
Operating pressure	1.0MPa
Reset pressure	0.3MPa

Directions for use

- When installing the valve on a junction side, screw it into place with a wrench applied to the valve body
- When connecting the valve to piping, turn bushing holding nipple with a wrench.



Available as service parts only. For new installations, please see MO-II valves.




[MO]

Model

Model	Part Number	Discharge volume (ml)	L (mm)	Mark	B
MO-1	205070	0.01	44.5	1	HEX12
MO-3	205071	0.03		3	
MO-5	205072	0.05		5	
MO-10	205073	0.1		10	
MO-20	205074	0.2	53.5	20	
MO-30	205075	0.3		30	
MO-50	205076	0.5	65	50	HEX19
MO-100	205077	1	74.5	100	
MO-150	205078	1.5		150	

Dimensional drawing



● Related parts



AMZ-III
: P.93



AMO-III DS
: P.97



AMO-II -150S
: P.99



AMI-300S · 1000S
: P.101



Tubing
: P.171



Adapters
: P.175



Compression parts
: P.169



Push-in Fitting
: P.182



Pressure switch
: P.163



Ludo-sensor
: P.164